

WHAT IS CLAIMED IS:

1. A developing cartridge detachably mountable to a main assembly of an electrophotographic image forming apparatus, said apparatus comprising:

5 a cartridge frame;

 a developing roller for developing an electrostatic latent image formed on an electrophotographic photosensitive drum;

 an one-end frame groove provided at one
10 longitudinal end of said cartridge frame;

 an one-end frame projection provided at said one longitudinal end of said cartridge frame;

 one-end bearing member for rotatably supporting one-end shaft provided at one longitudinal
15 end of said developing roller extended in a longitudinal direction of said cartridge frame;

 an one-end bearing member cylinder, provided on said one-end bearing member, engaged with an inner surface of said one-end frame groove;

20 an elongated bearing member opening which is provided on said one-end bearing member and through which said frame one end projection is penetrated;

 a first projection of metal provided on an outer surface of said one-end bearing member opposite
25 from an inner side surface on which said one-end bearing member cylinder is provided;

 a second projection of metal which is

provided on said one-end bearing member and which supports a gear for receiving a driving force from a main assembly of the apparatus when said cartridge is mounted to the main assembly of the apparatus;

5 a first screw for securing said one-end bearing member to one end of said cartridge frame;

 an one-end side cover provided at one longitudinal end of said cartridge frame and covering said one-end bearing member;

10 a first opening provided in said one-end side cover and engageable with said first projection;

 a second opening provided in said one-end side cover and engageable with said second projection;

 an one-end side cover projection provided
15 inside said one-end side cover and engageable with an inner surface of a one-end bearing member cylinder engaged with said one-end frame groove;

 a second screw for securing said one-end side cover to one end of said cartridge frame; and

20 a third screw for securing said one-end side cover to said first projection provided on said one-end bearing member.

2. A developing cartridge according to Claim 1,
25 further comprising an application roller for applying a developer on said developing roller, wherein said one-end bearing member is provided with shaft

projection opening for permitting projection of a shaft provided on one end of said application roller.

3. A developing cartridge according to Claim 1
5 or 2, further comprising a one-end guide, on an outer surface opposite from an inner surface on which said one-end side cover projection is provided, for guiding said developing cartridge when said developing cartridge is mounted to the main assembly of the
10 apparatus.

4. A developing cartridge according to Claim 3, further comprising, on said one-end side cover, a retainer opening through which one end of a retaining
15 portion for preventing said developing cartridge from disengaging from the main assembly of the apparatus when said developing cartridge is mounted to the main assembly of the apparatus, is retractably projected.

20 5. A developing cartridge detachably mountable to a main assembly of an electrophotographic image forming apparatus, said apparatus comprising:
a cartridge frame;
a developing roller for developing an
25 electrostatic latent image formed on an electrophotographic photosensitive drum;
a driving force receiving member, provided at

one longitudinal end of said cartridge frame, for receiving a driving force from the main assembly of the apparatus when said developing cartridge is mounted to the main assembly of the apparatus;

5 an other-end frame groove provided at another longitudinal end of said cartridge frame;

 an other-end frame projection provided at said other longitudinal end of said cartridge frame;

 other-end bearing member for rotatably
10 supporting other-end shaft provided at other longitudinal end of said developing roller extended in a longitudinal direction of said cartridge frame;

 an other-end bearing member cylinder, provided on said other-end bearing member, engaged
15 with an inner surface of said other-end frame groove;

 an elongated bearing member opening which is provided on said other-end bearing member and through which said frame other end projection is penetrated;

 a first screw for securing said other-end
20 bearing member to another end of said cartridge frame;

 an other-end side cover provided at another longitudinal end of said cartridge frame and covering said one-end bearing member;

 an other-end side cover projection provided
25 inside said other-end side cover and engageable with an inner surface of an other-end bearing member cylinder engaged with said other-end frame groove;

an other-end side cover cylinder provided on said other-end side cover and having an inner surface which is engaged with an other-end frame projection penetrated through said bearing member opening;

5 a second screw for securing said other-end side cover to the other end of said cartridge frame; and

 a third screw for securing said other-end bearing member and said other-end side cover to the
10 other end of said cartridge frame.

6. A developing cartridge according to Claim 5, further comprising an application roller for applying a developer on said developing roller, wherein said
15 other-end bearing member is provided with a shaft projection opening for permitting a shaft provided on the other end of said application roller to penetrate, and further comprising a toner seal opening for permitting a toner seal for unsealably sealing a
20 developer supply opening provided in a developer accommodating portion for accommodating the developer to be pulled.

7. A developing cartridge according to Claim 6,
25 further comprising, on an outer surface opposite from an inner surface on which said other-end side cover projection is provided, other-end guide for guiding

said developing cartridge when said developing
cartridge is mounted to the main assembly of the
apparatus, and a toner seal opening for permitting a
toner seal for unsealably sealing a developer supply
5 opening provided in a developer accommodating portion
for accommodating the developer to be pulled.

8. A developing cartridge according to Claim 7,
further comprising, on said other-end side cover, a
10 retainer opening through which one end of a retaining
portion for preventing said developing cartridge from
disengaging from the main assembly of the apparatus
when said developing cartridge is mounted to the main
assembly of the apparatus, is retractably projected.

15

9. A method for mounting a one-end side cover on
a cartridge frame, comprising:

an one-end shaft supporting step of rotatably
supporting, on a one-end bearing member, a one-end
20 shaft provided at one longitudinal end of a developing
roller;

an one-end bearing member cylinder engagement
step of engaging a one-end bearing member cylinder
provided on a one-end bearing member with a one-end
25 frame groove provided at one longitudinal end of
cartridge frame to mount a one-end bearing member on
the cartridge frame;

a frame one-end projection penetration step
of penetrating a one-end frame projection provided at
one longitudinal end of cartridge frame through a
bearing member opening provided in the one-end bearing
5 member to mount the one-end bearing member on the
cartridge frame;

an one-end bearing member securing step of
screwing a screw into a screw bore provided in the
cartridge frame through the opening provided in the
10 one-end bearing member to secure the one-end bearing
member on the cartridge frame;

an one-end side cover projection engaging
step of engaging a one-end side cover projection
provided on the one-end side cover with an inner
15 surface of an end bearing member cylinder engaged with
a one-end frame groove;

a first projection engagement step of
engaging a first projection of metal provided on one-
end bearing member with a first opening provided in
20 one-end side cover;

a second projection engagement step of
engaging a second projection of metal provided on the
one-end bearing member with a second opening provided
in one-end bearing member;

25 a first one-end side cover screwing step of
screwing a screw into a screw bore provided in the
cartridge frame through an opening provided in the

one-end side cover to screw the one-end side cover to the cartridge frame; and

5 a second one-end side cover screwing step of screwing a screw into a screw bore provided in the first projection provided in the one-end bearing member through an opening provided in the one-end side cover.

10 10. A method according to Claim 9, further comprising a shaft projection step of projecting a shaft provided at one end of an application roller for applying the developer on the developing roller through a shaft projection opening provided on the one-end bearing member when the one-end bearing member
15 is mounted to the cartridge frame.

20 11. A method according to Claim 10, further comprising a retainer member projecting step of projecting one end of a retaining member for preventing the developing cartridge from disengaging from the apparatus through a retaining member hole, when the one-end side cover is mounted to the cartridge frame, and the developing cartridge is mounted to the main assembly of the apparatus.

25

12. A method for mounting a one-end side cover on a cartridge frame, comprising:

an other-end shaft supporting step of rotatably supporting, on an other-end bearing member, an other-end shaft provided at another longitudinal end of a developing roller;

5 an other-end bearing member cylinder engagement step of engaging an other-end bearing member cylinder other-end bearing member provided on an other-end bearing member with an other-end frame groove provided at another longitudinal end of
10 cartridge frame to mount an other-end bearing member on the cartridge frame;

a frame other-end projection penetration step of penetrating an other-end frame projection provided at another longitudinal end of cartridge frame through
15 a bearing member opening provided in the other-end bearing member to mount the other-end bearing member on the cartridge frame;

an other-end bearing member securing step of screwing a screw into a screw bore provided in the
20 cartridge frame through the opening provided in the other-end bearing member to secure the other-end bearing member on the cartridge frame;

an other-end side cover projection engagement step of engaging an other-end side cover projection
25 provided on the other-end side cover on an inner surface of an other-end bearing member cylinder engaged with an other-end frame groove;

an other-end side cover cylinder engaging
step of engaging an other-end side cover cylinder with
an other-end frame projection penetrating through the
other-end bearing member opening;

5 a first other-end side cover screwing step of
screwing a screw into a screw bore provided in the
cartridge frame through an opening provided in the
other-end side cover to screw the other-end side cover
to the cartridge frame; and

10 a second other-end side cover screwing step
of screwing a screw into a screw bore provided in the
first projection provided in the the-end bearing
member through an opening provided in the other-end
side cover.

15 13. A method according to Claim 12, further
comprising a shaft projection step of projecting a
shaft provided on another end of an application roller
for applying the developer on the developing roller
20 through a shaft projection opening shaft projected in
the provision.

 14. A method according to Claim 12 or 13, further
comprising a retainer member projecting step of
25 projecting one end of a retaining member for
preventing the developing cartridge from disengaging
from the apparatus through a retaining member hole,

when the one-end side cover is mounted to the cartridge frame, and the developing cartridge is mounted to the main assembly of the apparatus, and a toner seal projection step of projecting a toner seal
5 for unsealably sealing a developer supply opening provided in a developer accommodating portion for accommodating the developer through a toner seal opening.

10 15. An electrophotographic image forming apparatus for forming an image on a recording material, to which apparatus a developing cartridge is detachably mountable, comprising:

(i) an electrophotographic photosensitive
15 drum;

(ii) a mounting portion for detachably mounting a developing cartridge, which includes a cartridge frame;

a developing roller for developing an
20 electrostatic latent image formed on said electrophotographic photosensitive drum;

an one-end frame groove provided at one longitudinal end of said cartridge frame;

an one-end frame projection provided at said
25 one longitudinal end of said cartridge frame;

one-end bearing member for rotatably supporting one-end shaft provided at one longitudinal

end of said developing roller extended in a longitudinal direction of said cartridge frame;

an one-end bearing member cylinder, provided on said one-end bearing member, engaged with an inner surface of said one-end frame groove;

an elongated bearing member opening which is provided on said one-end bearing member and through which said frame one end projection is penetrated;

a first projection of metal provided on an outer surface of said one-end bearing member opposite from an inner side surface on which said one-end bearing member cylinder is provided;

a second projection of metal which is provided on said one-end bearing member and which supports a gear for receiving a driving force from a main assembly of the apparatus when said cartridge is mounted to the main assembly of the apparatus;

a first screw for securing said one-end bearing member to one end of said cartridge frame;

an one-end side cover provided at one longitudinal end of said cartridge frame and covering said one-end bearing member;

a first opening provided in said one-end side cover and engageable with said first projection;

a second opening provided in said one-end side cover and engageable with said second projection;

an one-end side cover projection provided on

an inside of said one-end side cover and engaged with
an inner surface of a one-end bearing member cylinder
engaged with said frame positioning hole;

a second screw for securing said one-end side
5 cover to one end of said cartridge frame; and

a third screw for securing said one-end
bearing member to said first projection provided on
said one-end bearing member.

10 16. An electrophotographic image forming
apparatus for forming an image on a recording
material, to which apparatus a developing cartridge is
detachably mountable, comprising:

(i) an electrophotographic photosensitive
15 drum;

(ii) a mounting portion for detachably
mounting a developing cartridge, which includes
a cartridge frame;

a developing roller for developing an
20 electrostatic latent image formed on an
electrophotographic photosensitive drum;

a driving force receiving member, provided at
one longitudinal end of said cartridge frame, for
receiving a driving force from the main assembly of
25 the apparatus when said developing cartridge is
mounted to the main assembly of the apparatus;

an other-end frame groove provided at another

longitudinal end of said cartridge frame;

an other-end frame projection provided at
said other longitudinal end of said cartridge frame;

other-end bearing member for rotatably
5 supporting other-end shaft provided at other
longitudinal end of said developing roller extended in
a longitudinal direction of said cartridge frame;

an other-end bearing member cylinder,
provided on said other-end bearing member, engaged
10 with an inner surface of said other-end frame groove;

an elongated bearing member opening which is
provided on said other-end bearing member and through
which said frame other end projection is penetrated;

a first screw for securing said other-end
15 bearing member to another end of said cartridge frame;

an other-end side cover provided at another
longitudinal end of said cartridge frame and covering
said one-end bearing member;

an other-end side cover projection provided
20 inside said other-end side cover and engageable with
an inner surface of an other-end bearing member
cylinder engaged with said other-end frame groove;

an other-end side cover cylinder provided on
said other-end side cover and having an inner surface
25 which is engaged with an other-end frame projection
penetrated through said bearing member opening;

a second screw for securing said other-end

side cover to the other end of said cartridge frame;
and

a third screw for securing said other-end
bearing member to said first projection provided on
5 said other-end bearing member.

10

15

20

25